

POLAR BLACK

Változat
Sziget 35 cm - Fekete - 800 m³/h

Kollekció
Design

EAN kód
8034122354613



A fénykép csak tájékoztató jellegű
Lehet, hogy nem felel meg a kiválasztott változatnak.

JELLEMZŐK

Elektronikus vezérlés
LED-világítás
Eltávolítható és mosható felső
szűrő
Szénszűrő mellékelve

OPCIONÁLIS TARTOZÉKOK

KACL.770#41F
Tető alatti távirányítós motor1100 m3/h
kefe nélküli

KACL.786#41F
Kültéri elszívó ventilátor 1000 m3/h

KACL.796#4AF
Kültéri elszívó ventilátor 1500 m3/h

KACL.797#4AF
Tető alatti távirányítós motor 1300
m3/h

KACL.798#41F
Tető alatti távirányítós motor 950 m3/h

103050091
Kerek szénzsűrő, Ø170 mm - 6-os
típus

MŰSZAKI JELLEMZŐK

Felszerelés mód
Sziget

Méret
35 cm

Kivitel
Festett fehér acél

Motor
800 m³/h

Vezérlés típusa
Elektronikus vezérlés

Sebességfokozatok
4

Világítás
Led 3x1,2 W - 3200 K

Szénzsűrő
Kerek szénzsűrő, Ø170 mm - 6-os
típus (opcionális)

Minimális távolság
Gáz főzőlaptól: 60 cm
Elektromos főzőlaptól: 52 cm

CSOMAGOLÁS: SÚLYOK ÉS
TÉRFOGATOK

Bruttó súly
30 kg

Nettó súly
24 kg

Térfogat
0,3 m³

Csomagolás mérete
Hossz
995 mm
Magasság
500 mm
Mélység
595 mm

FOGYASZTÁS ÉS
CSATLAKOZÁSI JELLEMZŐK

Maximális fogyasztás
280 W

Feszültség
220-240V

Frekvencia
50 - 60 Hz

Csatlakozó típusa
Schuko

MOTOR MŰSZAKI ADATLAP


Maximális kapacitás
710 m³/h
I.E.C. 61591

Maximális zajszint
68 dB(A)re1pW
I.E.C. 60704-2-13

Maximum nyomás (Pa)
500 Pa

Motor max. teljesítménye
215 W

ENERGIAOSZTÁLY
B



POLAR BLACK

Változat
Sziget 35 cm - Fekete - 800 m³/h


Kollekció
Design

EAN kód
8034122354613

MOTOR MŰSZAKI ADATLAP

Motor fordulatszáma	1	2	3	4
Zajszint dB(A)re1pW-I.E.C. 60704-2-13	48	54	61	67
Kapacitás (m³/h) I.E.C.61591	290	380	490	710
Maximum nyomás (Pa)	400	450	480	500
Motor teljesítménye (W)	134	156	180	215
Légkifúvás	150	150	150	150

KAPACITÁS / NYOMÁS




POLAR BLACK

Változat
Sziget 35 cm - Fekete - 800 m³/h

Kollekció
Design

EAN kód
8034122354613

ENERGIACÍMKE



PF		
S	Falmec Spa	
M	Sziget 35 cm - Fekete - 800 m³/h	
AEC	61,4	kWh/év
EEC	B	
FDE	28,1	
FDEC	A	
LE	24,2	
LEC	B	
GFE	76,0	
GFEC	C	
Qmin	290,0	m³/h
Qmax	490,0	m³/h
Qboost	710,0	m³/h
SPEmin	48	dBa
SPEmax	61	dBa
SPEboost	67	dBa
PO	-	W
PS	0,48	W
PI		
F	1	
EEL	59,6	
Qbep	371,0	m³/h
Pbep	412	Pa
Qboost	710,0	m³/h
Wbep	151,0	W
WL	8,60	W
Emiddle	208	lex
Lwa-SPEmax	61	dBa

PF_Termékismertető adatlap az EU65/2014 szerint S_Szállító neve / M_Modell azonosítója / AEC_Éves energiafogyasztás (AEC hood) / EEC_Energiahatékonysági osztály / FDE_Folyadékdinamikai hatékonyság (FDE hood) / FDEC_Folyadékdinamikai hatékonysági (FDE) osztály / LE_Világítás hatékonyság (LE hood) / LEC_Világítás hatékonysági osztály / GFE_Zsírszűrési hatékonyság / GFEC_Zsírszűrési hatékonyság / Qmin_Légáram (m³/h) minimum sebességen normál használat esetén / Qmax_Légáram (m³/h) maximum sebességen normál használat esetén / Qboost_Légáram intenzív/erős beállítás esetén (m³/h) (Max. légáram) / SPEmin_Légi akusztikai A-súlyozott hangteljesítmény-kibocsátás minimális sebességnél, normál használat esetén / Légi akusztikai A-súlyozott hangteljesítmény-kibocsátás minimális sebességnél, normál használat esetén / SPEboost_Légi akusztikai A-súlyozott hangteljesítmény-kibocsátás(dB) intenzív vagy turbó sebességnél/ PO_Energiafogyasztás kikapcsolt módban (Po) / Ps_Energiafogyasztás készenléti módban (Ps). PI_További információk a 66/2014 szerint F_Időnövelő tényező / EEL_Energiahatékonysági index / Qbep_Mért légáramlási sebesség a legjobb hatékonysági ponton / Pbep_Mért légnyomás a legjobb hatékonysági ponton / Qboost_Maximum légáram / Wbep_Mért elektromos teljesítmény a legjobb hatékonysági ponton / WL_Világítási rendszer névleges teljesítménye / Emiddle_A világítási rendszer átlagvilágítása a főzőfelületen / Lwa=SPEmax_Hangnyomásszint a legnagyobb sebességen.

POLAR BLACK

Version
Island 35 cm - Black - 800 m³/h

Collection
Design

EAN code
8034122354613



The photograph is purely for information
It may not correspond to the selected version.

FEATURES

- Electronic control
- LED lighting
- Top filter, removable and washable
- Charcoal filter included

OPTIONAL ACCESSORIES

- KACL.770#41F**
Remote under-roof 1100 m3/h
Brushless
- KACL.786#41F**
Outdoor extractor fan 1000 m3/h
- KACL.796#4AF**
Outdoor extractor fan 1500 m3/h
- KACL.797#4AF**
Remote under-roof motor 1300 m3/h
- KACL.798#41F**
Remote under-roof motor 950 m3/h
- 103050091**
Round charcoal filter Ø170 mm - Type 6

TECHNICAL FEATURES

- Installation type**
Island
- Dimensions**
35 cm
- Finishing**
Painted black steel
- Motor**
800 m³/h
- Type of control**
Electronic control
- Speed settings**
4
- Lighting**
Led 3x1,2 W - 3200 K
- Charcoal filter**
Round charcoal filter Ø170 mm - Type 6 (optional)
- Minimum distance**
Gas hob: 60 cm
Electric hob: 52 cm

PACKAGING:WEIGHTS AND VOLUMES


- Gross weight**
30 kg
- Net weight**
24 kg
- Volumes**
0.3 m³
- Packaging size**
Length
995 mm
Height
500 mm
Depth
595 mm

CONSUMPTION AND CONNECTION FEATURES

- Maximum consumption**
280 W
- Voltage**
220-240V
- Frequency**
50-60Hz
- Plug type**
Shuko

MOTOR TECHNICAL SHEET

- Maximum capacity**
710 m³/h
I.E.C. 61591
- Maximum noise level**
67 dB(A)re1pW
I.E.C.60704-2-13
- Maximum pressure (Pa)**
500 Pa
- Max. motor power**
215 W
- ENERGY CLASS**
B



POLAR BLACK

Version
Island 35 cm - Black - 800 m³/h


Collection
Design

EAN code
8034122354613

MOTOR TECHNICAL SHEET

Motor speed	1	2	3	4
Noise level dB(A)re1pW-I.E.C.60704-2-13	48	54	61	67
Capacity (m3/h) I.E.C.61591	290	380	490	710
Maximum pressure (Pa)	400	450	480	500
Motor Power (W)	134	156	180	215
Air outlet	150	150	150	150

CAPACITY / PRESSURE




POLAR BLACK

Version
Island 35 cm - Black - 800 m³/h

Collection
Design

EAN code
8034122354613

ENERGY LABEL



PF		
S	Falmec Spa	
M	Island 35 cm - Black - 800 m³/h	
AEC	61,4	kWh/a
EEC	B	
FDE	28,1	
FDEC	A	
LE	24,2	
LEC	B	
GFE	76,0	
GFEC	C	
Qmin	290,0	m³/h
Qmax	490,0	m³/h
Qboost	710,0	m³/h
SPEmin	48	dBa
SPEmax	61	dBa
SPEboost	67	dBa
PO	-	W
PS	0,48	W
PI		
F	1	
EEL	59,6	
Qbep	371,0	m³/h
Pbep	412	Pa
Qboost	710,0	m³/h
Wbep	151,0	W
WL	8,60	W
Emiddle	208	lux
Lwa-SPEmax	61	dBa

PF_Product fiche according to 65/2014 S_Supplier name / M_Model identification / AEC_Annual Energy Consumption (AEC hood) / EEC_Energy Efficiency class / FDE_Fluid Dynamic Efficiency (FDE hood) / FDEC_Fluid Dynamic Efficiency class / LE_Lighting Efficiency (LE hood) / LEC_Lighting Efficiency class / GFE_Grease Filtering Efficiency / GFEC_Grease Filtering Efficiency class / Qmin_Air flow (in m³/h) at min speed in normal use / Qmax_Air flow (in m³/h) at max speed in normal use / Qboost_Air flow (in m³/h) at intensive or boost setting (max air-flow) / SPEmin_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost_Airborne acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / PO_Power consumption in off mode (Po) / Ps_Power consumption in stand by mode (Ps). **PI_Additional information according to 66/2014** F_Time increase factor / EEL_Energy Efficiency Index / Qbep_Measured air flow rate at best efficiency point / Pbep_Measured air pressure at best efficiency point / Qboost_Maximum air flow / Wbep_Measured electric power input at best efficiency point / WL_Nominal power of the lighting system / Emiddle_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax_Sound pressure level at the highest speed.